

REFERENCES

- [1] J. F. App, "Niobium (columbium) and tantalum," *2009 Minerals Yearbook, U.S. Geological Survey Reston*, vol. 52, pp. 1–14, 2011.
- [2] K. Mineta and T. Okabe, "Development of a recycling process for Tantalum from capacitor scraps," *Journal of Physics and Chemistry of Solids*, vol.66, no.2–4, pp. 318–321, 2015.
- [3] R. Shimizu, R. Hanazawa, and N. Morita, "Influence and Effect of Pyrolysis with Additives in Tantalum Capacitors," *International Journal of Environmental Science and Development*, vol. 13, no. 4, 2022.
- [4] M. Sasaki, S. Ishikawa, K. Nasu, A. T. Quitan, and M. Goto, "Recovery of Tantalum from capacitor with solvothermal treatment," in *Proc. ISFR2011*, 2011, pp. 147–148.
- [5] Y. Shoji, M. Hodotsuka, and K. Yamamoto, "Molten salt waste disposal equipment for organic Halogen compounds," *Toshiba Review*, vol. 58, no. 5, pp. 50–53, 2003.
- [6] T. Bhaskar, T. Matsui, J. Kaneko, M. A. Uddin, A. Muto, and Y. Sakata, "Novel calcium based sorbent (Ca–C) for the dehalogenation (Br, Cl) process during halogenated mixed plastic (PP/PE/PS/PVC and HIPS-Br) pyrolysis," *Green Chem.*, vol.4, pp. 372–375, 2002.
- [7] M. Iazso', Z. Cze'ge'ny, and C. Csoma, "Pyrolysis and debromination of flame retarded polymers of electronic scrap studied by analytical pyrolysis," *Journal of Analytical and Applied Pyrolysis*, vol. 64, pp. 249–261, 2002.
- [8] T. Bhaskar, T. Matsui, M. A. Uddin, J. Kaneko, A. Muto, and Y. Sakata, "Effect of Sb₂O₃ in brominated Heating Impact Polystyrene (HIPS-Br) on thermal degradation and debromination by iron oxide carbon composite catalyst (Fe–C)," *Applied Catalysis B*, vol. 43, pp. 229–241, 2003.
- [9] G. Grause, J. Ishibashi, T. Kameda, T. Bhaskar, and T. Yoshioka, "Kinetic studies of the decomposition of flame retardant containing high-impact polystyrene," *Polym. Degrad. Stab.*, vol. 95, pp. 1129–1137, 2010.
- [10] C. Vasile, M. A. Brebu, T. Karayildirim, J. Yanik, and H. Darie, "Feedstock recycling from plastics and thermosets fractions of used computers. II. Pyrolysis oil upgrading," *Fuel*, vol. 86, no. 4, pp. 477–485, 2007.
- [11] B. Niu, "Application of pyrolysis to recycling organics from waste tantalum capacitors," *Journal of Hazardous Materials*, vol. 335, pp. 39–46, 2017.
- [12] Y. Liu, "Impact of the operating conditions on the derived products and the reaction mechanism in vacuum pyrolysis treatment of the organic material in waste integrated circuits," *Journal of Cleaner Production*, vol. 197, pp. 1488–1497, 2018.
- [13] S. Katano, "Recovery of Tantalum sintered compact from used Tantalum condenser using steam gasification with Sodium hydroxide," *APCBEE Procedia*, vol. 10, pp. 182–186, 2014.
- [14] N. Morita, M. Nakayasu, A. T. Saito, T. Wajima, and H. Nakagome, "Effect of hydrotalcite on Bromine content in oil produced from the pyrolysis of Acrylonitrile-Butadiene-Styrene plastics," *International Journal of Chemical Engineering and Applications*, vol. 7, no.4, pp. 23–27, 2016.
- [15] T. Kameda, M. Nakamura, and T. Yoshioka, "Removal of antimonate ions from an aqueous solution by anion exchange with magnesium–aluminum layered double hydroxide and the formation of a brandholzite-like structure," *Journal of Environmental Science and Health, Part A*, vol. 47, pp. 1146–1151, 2012.
- [16] T. Bhaskar, T. Matsui, J. Kaneko, M. A. Uddin, A. Muto, and Y. Sakata, "Novel calcium based sorbent (Ca–C) for the dehalogenation (Br, Cl) process during halogenated mixed plastic (PP/PE/PS/PVC and HIPS-Br) pyrolysis," *Green Chem.*, vol. 4, pp. 372–375, 2002.
- [17] K. Hanazawa, M. Toritsuka, and N. Morita, "Effects of adding hydrotalcite with different compositional ratios in the pyrolysis treatment of brominated plastics," *International Journal of Chemical Engineering and Applications*, vol. 12, no. 1, 2021.
- [18] Y. Sato, Y. Kodera, and T. Kamo, "Effect of solvents on the liquid-phase cracking of thermosetting resins," *ENERGY & FUELS*, vol. 13, no. 2, pp. 364–368, 1999.
- [19] Y. Sato, Y. Kodera, T. Kamo, H. Yamaguchi, and K. Tatsumoto, "Removal of chlorine from waste PVC and conversion to useful chemicals," *Prospects for Coal Science in the 21st Century*, vols I and II, pp. 705–708, 1999.
- [20] T. Kameda, N. Uchiyama, and T. Yoshioka, "Removal of HCl, SO₂, and NO by treatment of acid gas with Mg–Al oxide slurry," *Chemosphere*, vol. 82, pp. 587–591, 2011.
- [21] T. Kameda, N. Uchiyama, and T. Yoshiok, "Treatment of gaseous hydrogen chloride using Mg–Al layered double hydroxide intercalated with carbonate ion," *Chemosphere*, vol. 80, pp. 658–662, 2010.
- [22] T. Kameda, M. Nakamura, and T. Yoshioka, "Removal of antimonate ions from an aqueous solution by anion exchange with magnesium–aluminum layered double hydroxide and the formation of a brandholzite-like structure," *Journal of Environmental Science and Health, Part A*, vol. 47, pp. 1146–1151, 2012.
- [23] K. Morimoto, S. Anraku, J. Hoshino, T. Yoneda, and T. Sato, "Surface complexation reactions of inorganic anions on hydrotalcite-like compounds," *Journal of Colloid and Interface Science*, vol. 384, pp. 99–104, 2012.
- [24] Y. Sun, "Catalytic oxidation performances of typical oxygenated volatile organic compounds (acetone and acetaldehyde) over MAIO (M = Mn, Co, Ni, Fe) hydrotalcite-derived oxides," *Catalysis Today*, vol. 327, pp. 389–397, 2019.
- [25] R. M. Navarro, "Catalytic fast pyrolysis of biomass over Mg–Al mixed oxides derived from hydrotalcite-like precursors: Influence of Mg/Al ratio," *Journal of Analytical and Applied Pyrolysis*, vol. 134, pp. 362–370, 2018.

Copyright © 2024 by the authors. This is an open access article distributed under the Creative Commons Attribution License which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).